

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES PATENT

MOTION SENSING SYSTEMS AND METHODS

INVENTORS

Jimmy A. Tatum
701 Shallow Creek Lane
Plano, TX 75025

Citizen of the United States of America

James K. Guenter
214 Coral Ridge Road
Garland, TX 75044

Citizen of the United States of America

EXPRESS MAIL NO.: EL597436611US

MOTION SENSING SYSTEMS AND METHODS

TECHNICAL FIELD

The present invention relates generally to the field of sensing. More specifically, the present invention relates generally to multiple laser optical sensing systems and methods. The present invention further relates to motion detection systems and methods.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208

BACKGROUND OF THE INVENTION

Previous approaches to addressing sensing needs have generally involved using a single light signal from a light source, such as a light emitting diode, and multiple detectors. In order to illuminate a large area in an environment using a single light source, two general methods are known. One approach typically involves emitting a broad light signal from the light source and detecting the signal with one of multiple detectors positioned throughout the environment. The other approach typically involves emitting a narrow light signal from the light source, spreading the signal around the environment by reflecting it off of a rotating mirror, for instance, and detecting the signal with one of multiple detectors positioned throughout the environment. While feasible, both approaches typically require multiple detectors and are usually not power efficient as a result, yielding a low signal-to-noise ratio. A poor power-transfer ratio reflects this inefficiency as the individual detector that receives a light signal usually detects only a portion of the signal that was originally emitted. Consequently, the signal that was detected generally provides only limited information about a target being sensed in the environment. These approaches also tend to limit the size range of the target being sensed in an environment due to the nature of the single light signal.

The limitations of these previous approaches are often manifested in applications such as detecting the motion of a target in an environment. Many motion detection systems generally involve a line-of-sight operation, where at least one detector detects the motion of a target as the target breaks a beam of light emitted from a light source. In relatively simple applications, such as determining the presence or absence of a target, this approach generally suffices. For more complex applications, such as determining the direction of the target's motion, this approach proves less adequate. When a target moves across a single light signal emitted by a light source, the signal received by a

detector gradually decreases as the signal blocked by the target gradually increases. This gradual change in signal detection typically requires a complex algorithm to determine the position of the target in the environment. Adding multiple detectors can provide more information and decrease the complexity of the algorithm required, though introduces power inefficiencies as mentioned previously, as well as added cost associated with additional hardware.

The limitations of the aforementioned approaches also relate to applications involving target recognition. Many known systems, either for recognizing only specific targets or for mapping spatial characteristics of targets, involve spreading a light signal with a rotating mirror and/or using multiple detectors. Holograms can also be used to spread the light signal by dividing the signal into smaller light signals. An approach for detecting only specific targets involves emitting pulses of signals from a transceiver, receiving the signals that reflect off of a target, and comparing the received signals with preset signals reflected off of known targets. Information about the known objects is typically stored in a database. An approach for mapping a target involves superimposing light signals received by different detectors in the presence of a target and comparing the signals with respect to signals associated with the environment without the target.

While each of these approaches is feasible for a particular function, none is known to perform several functions. This deficit creates a need for a versatile system that is both power efficient and cost effective. Such a system could be capable of, for instance, detecting the presence or absence of any target or of a specific target, detecting the spatial characteristics of a target, detecting the motion of any target or a specific target, or detecting various characteristics about the motion of a target.

BRIEF SUMMARY OF THE INVENTION

The following summary of the invention is provided to facilitate an understanding of some of the innovative features unique to the present invention, and is not intended to be a full description. A full appreciation of the various aspects of the invention can be gained by taking the entire specification, claims, drawings, and abstract as a whole.

An aspect of the present invention provides a laser-based sensing system that can be used in an environment to detect the motion of only "key"-shaped objects, ignoring others that can move about through a monitored environment. Different signals will reach a detector depending on the shape of particular targets present within the environment. The difference subsequently could allow for recognition of a specified target when a specified "match" is made.

Another aspect of the present invention includes a trainable multiple laser optical sensing system for detecting target characteristics using a vertical cavity surface-emitting laser. The system can include a vertical cavity surface emitting laser structure with at least two emission apertures that could be defined by photolithography. A laser signal can be emitted into an environment from each of the emission apertures. The system can also include at least one detector that is operationally responsive to the vertical cavity surface emitting laser structure. The system can include a microprocessor that is operationally coupled to the detector(s).

The system can include a memory for storing target data and a training module for allowing the system to be trained to recognize targets. In operation, the vertical cavity surface emitting laser structure can emit at least two laser signals into the environment, which may be occupied by a target in motion. At least one detector detects the laser signals once they have passed through the environment. The microprocessor can then determine target characteristics based on laser signals received by the detector(s) and comparison with known target data stored in

memory. Within the same vertical cavity surface emitting laser structure, the laser signals emitted can be identical or not identical. Optics can also be added to the system, such that laser signals pass through at least one lens or reflect off of a mirror or mirrors after exiting the emission apertures.

An aspect of the present invention provides methods for detecting target characteristics transmissively or reflectively using a vertical cavity surface-emitting laser. In a transmissive method, a vertical cavity surface emitting laser structure can statically emit at least two laser signals into an environment, which may be occupied by a target. The target in motion can block at least one of the laser signals as it is passing through the environment, and at least one detector can transmissively receive any of the signals not blocked by the target. A microprocessor can then determine target characteristics by comparing characteristics of the laser signals emitted by the vertical cavity surface emitting laser structure with characteristics of the signals received by the detector(s).

In a reflective method, a vertical cavity surface emitting laser structure can serially emit at least one laser signal at a time into an environment, which may be occupied by a target in motion. At least one of the laser signals can reflect off of the target and can be detected by at least one detector. A microprocessor can then determine target characteristics by comparing temporal characteristics of the laser signals emitted by the vertical cavity surface emitting laser structure with temporal characteristics of the signals received by the detector(s).

In any method taught by the present invention, a microprocessor could determine the motion of a target based on attributes such as its size or shape and/or by determining which laser signals are received by a detector after different arrays of laser signals are emitted by a vertical cavity surface emitting laser structure. The microprocessor could also detect motion of the target in an environment by detecting

changes in the array of laser signals that are blocked or reflected off of the target.

The novel features of the present invention will become apparent to those of skill in the art upon examination of the following detailed description of the invention or can be learned by practice of the present invention. It should be understood, however, that the detailed description of the invention and the specific examples presented, while indicating certain embodiments of the present invention, are provided for illustration purposes only because various changes and modifications within the scope of the invention will become apparent to those of skill in the art from the detailed description of the invention and claims that follow.

[illegible]

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying figures, in which like reference numerals refer to identical or functionally-similar elements throughout the separate views and which are incorporated in and form part of the specification, further illustrate the present invention and, together with the detailed description of the invention, serve to explain the principles of the present invention.

FIG. 1 illustrates a diagram of a vertical cavity surface emitting laser structure;

FIG. 2 illustrates diagrams of a vertical cavity surface emitting laser structure emitting two different patterns of light signals 2(a) and 2(b);

FIG. 3 illustrates a diagram of a target blocking a light signal statically emitted from a vertical cavity surface emitting laser structure before it reaches a detector;

FIG. 4 illustrates diagrams of a vertical cavity surface emitting laser structure cycling through different emission patterns of light signals to determine a map of the target. In 4(a) light signals forming a vertical line are blocked by a vertical bar-shaped target and none reach a detector. When a different pattern of signals is emitted as in 4(b), forming a right angle, one signal reaches the detector. In the presence of a right angle-shaped target as in 4(c), however, the same right angle-shaped pattern as emitted in 4(b) would be blocked;

FIG. 5 illustrates diagrams of a vertical cavity surface emitting laser

structure emitting the same pattern of light signals in 5(a) and 5(b). In 5(a) a target blocks all emitted signals, whereas in 5(b) a different target does not block all signals, allowing recognition of a specified target only;

FIG. 6 illustrates diagrams of emitted light signals passing through 6(a) a single lens producing a magnified image of the emitted array and 6(b) a compound lens system producing an expanded version of the emitted array;

FIG. 7 illustrates diagrams of emitted light signals passing through arrays of lenses. The array of lenses in 7(a) expands the diameter of light signals without changing their center spacing. The array of lenses in 7(b) expands the diameter and changes the direction of emitted light signals;

FIG. 8 illustrates a diagram of a target blocking a light signal serially emitted from a vertical cavity surface emitting laser structure before it reaches a detector;

FIG. 9 illustrates how a lens can be used to spread light signals emitted by a vertical cavity surface emitting laser structure into an environment occupied by a target, wherein an emitted signal reflects off of the target and reaches the detector;

FIG. 10 illustrates a system for the present invention; and

FIG. 11 illustrates a flow chart of a method for the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The particular values and configurations discussed in these non-limiting examples can be varied and are cited merely to illustrate an embodiment of the present invention and are not intended to limit the scope of the invention.

In the following nonlimiting example of this embodiment, FIG. 1 shows a vertical cavity surface emitting laser (VCSEL) structure 2 with a plurality of emission apertures 4, 6, 8, and 10. Emission apertures 4 can be fabricated by using either proton isolation or dielectric oxide techniques to provide both carrier and optical confinement. Emission aperture 4, for instance, is functionally integrated (although they do not have to be integrated) with a bond pad 12 and is electrically coupled to an element 14. Elements 16, 18, and 20 are also shown and can be identical or not identical to each other and to element 14. Upon powering elements, emission apertures emit light signals (not shown) perpendicular to VCSEL structure 2, making them especially amenable to the fabrication of both one and two-dimensional arrays.

While the example shown in FIG. 1 (and other figures) comprises a 2x2 array of emission apertures, it should be noted that the fabrication of MxN arrays is also feasible and that the 2x2 array is only provided to simplify explanation.

One of the principle advantages to array fabrication using VCSEL structures 2 is that all of the dimensions in the array can be fabricated using photolithography, thereby incorporating high dimensional tolerances in the placement of the emission apertures. As a result, the high dimensional tolerance produces a precisely defined array of light signals emitted and enables the fabrication of any one or two-dimensional array desired, such as the pattern of a cross. The elements can be electrically connected or coupled in virtually any manner desired as well, permitting light signals to be emitted individually or in groups. Light signals can be emitted in single or multiple spatial modes and can vary in terms of divergence angles and/or the diameter of the light signal being emitted and focused. Light signals can also be

emitted in single or multiple wavelengths. By using advanced selective epitaxial techniques, light signals of widely separated wavelengths can be fabricated.

FIG. 2 illustrates the illumination of different patterns of light signals by the same VCSEL structure 2. In FIG. 2(a), emission aperture 4 emits light signal 22 while aperture 8 emits light signal 26. In FIG. 2(b), emission aperture 6 emits light signal 24 while aperture 10 emits light signal 28. Similarly, any other one, or group of two, three, or four, light signals could be emitted from a 2x2 array. It should be reiterated that any array including any number of emission apertures could be constructed, permitting the emission of a variety of light signal patterns.

The first preferred embodiment is a reconfigurable static structured light source, which is depicted in FIG. 3. The diagram shows VCSEL structure 2 simultaneously emitting light signals 22 and 24 into an environment from emission apertures 4 and 6, respectively. While different light signals (or sets of signals) of the array can be emitted at different times, the timing of the changes is not directly relevant to the intended function. A target 30 is positioned in the environment between VCSEL structure 2 and a detector 32, which could be any of various types, such as a photodiode. A photodiode detector could either include an individual photodiode, multiple photodiodes individually packaged, or an array of photodiodes on a single structure in a single package.

As target 30 moves upward, the particular light signal received by detector 32 changes from full on (no obstruction), to half on (signal 24 blocked but not signal 22), and finally to full off (both signals 24 and 22 blocked). This happens in an essentially digital, or stepwise, fashion. A single illuminator in a similar geometry would provide only a very gradual change in detector illumination, requiring a more sophisticated algorithm to determine position at the midpoint. However, with this same VCSEL array, the identical function can be provided for

target 30 moving orthogonally to that shown in FIG. 3, simply by emitting signals from apertures 6 and 8 instead of 4 and 6, for example. For detection of a diagonally-moving target, signals from apertures 4 and 8 or 6 and 10 would be emitted. Thus, multiple motions could be sensed with a single detector 32 by sequentially emitting light signals from different apertures.

An extension of the concept requires larger element counts. Consider a VCSEL array with 5×2 elements, for example. If a stationary target with a corrugated edge is interposed between the VCSEL array and a detector, the corrugations will block some light signals and not others. By cycling through several fixed patterns of "lit" and "unlit" VCSELs, the detector signal can be interpreted as a map of the corrugated edge. In this way the corrugated obstruction acts as a key and the optical assembly including the VCSEL array and the detector acts as a lock. Electronics known to those skilled in the art can produce locks that recognize only one or several keys. Any emission patterns that correspond in a certain way to the pattern on the target would result in a positive identification, or recognition, by the detector.

FIG. 4 illustrates VCSEL structure 2 cycling through different emission patterns of light signals to determine a map of a target. In FIG. 4(a), a vertical bar-shaped target 34 blocks light signals 22 and 24 from reaching detector 32. When a different pattern of signals is emitted (22, 24, and 26) as in (b), signal 26 reaches detector 32 while signals 22 and 24 remain blocked. Detector 32, therefore, recognizes that target 34 has no horizontal piece spatially correlated to light signal 26. In the presence of a right angle-shaped target 36 as in FIG. 4(c), however, the same right angle-shaped pattern as emitted in FIG. 4(b) is blocked. Neither signal 22, 24, nor 26 reaches detector 32, indicating to detector 32 that target 36 (unlike target 34) does have a horizontal piece spatially correlated to light signal 26.

FIG. 5 illustrates how a specified target can be recognized while others are not. In this example, VCSEL structure 2 emits the same pattern of light signals in FIGS. 5(a) and (b), though the shape of the target differs. In FIG. 5(a), target 36 blocks all emitted signals 22, 24, and 26 from reaching detector 32. In FIG. 5(b), target 34 blocks only light signals 22 and 24, permitting signal 26 to reach detector 32. With the same pattern of light signals emitted, therefore, different signals will reach detector 32 depending on the shape of the particular target present in the environment. This difference subsequently could allow for recognition of a specified target when an exact "match" is made by the system.

The aforementioned corrugated opaque obstruction is only one example of possible key configurations. Among other possibilities are arrays of holes or exposed areas on film.

In addition to using a plurality of light sources, the present invention could perform object recognition tasks faster than many current systems by using a camera as a detector. The camera could be one of various types, including a charge-coupled device (CCD) or CMOS camera. When the camera display of a typical current system is divided into separate areas, complex image processing algorithms are often required to measure the partially blocked areas from the uniform light source. When the display of the present invention is divided into separate areas, each area has its own independent illumination differing spatially from adjacent illuminations due to the plurality of light signals emitted. As a result, all of the signals can be detected simultaneously and be quickly summed together to provide the desired information.

A target could also be detected by the composition of its surface. The absorptive characteristics of the surface can absorb and/or reflect light signals

differently based on the wavelength of the signals. Emitting light signals of different wavelengths, which might be accomplished by fabricating VCSEL structure 2 with different elements, could, therefore, also indicate the absorptive characteristics of the material. In either situation, detecting a target based on its characteristics, or detecting the characteristics of a target, a microprocessor could determine characteristics by comparing the light signals received by a detector with the signals emitted by a VCSEL structure. If the difference in wavelength among the signals emitted were large enough to detect by a detector, a plurality of detectors (such as detector 32 depicted in the figures) could be used to detect signals within different ranges of wavelength, which might provide more detailed information about the absorptive characteristics of most targets. Features can be compared to characteristics stored in memory..

In order to detect targets of various sizes, optics could be added. A lens or array of lenses can be positioned between VCSEL structure 2 and target 30 such that the lens reproduces the pattern of emitted light signals into a larger or smaller pattern in the image plane. The emission pattern of the image would be identical in shape to the original pattern emitted but different in size. A microprocessor could then correlate the pattern of light signals received by detector 32 in the presence of target 30 with the pattern of signals originally emitted and/or with signals stored in memory.

FIG. 6 illustrates two ways in which lenses can be used to alter the size of an array of light signals. In FIG. 6(a), a single lens 38 produces a magnified image 42 of the array emitted by VCSEL structure 2, affording detection of targets larger than the physical array. As light signal 24 enters lens 38, lens 38 magnifies signal 24 into a new light signal 40 having a larger diameter. In this particular configuration, magnified image 42 would be inverted compared to the array originally emitted by VCSEL structure 2. Two lenses could also be used in a collimator-telescope

configuration (not shown). In FIG. 6(b) a compound lens system produces an expanded version of the array emitted by VCSEL structure 2. As light signals 22 and 24 enter lens 44, lens 44 manipulates (either through convergence or divergence) signals 22 and 24, creating new light signals 46 and 48, respectively. Signals 46 and 48 then enter a lens 50, which collimates signals 46 and 48 into new signals 52 and 54, respectively. These resulting signals 52 and 54 have a larger diameter than light signals 22 and 24 originally emitted.

FIG. 7 illustrates alternative configurations of arrays of lenses that can be used to alter the array of light signals emitted by VCSEL structure 2. In FIG. 7(a) lens array 56 contains lenses 58, 60, 62, and 64 that correspond spatially to emission apertures 4, 6, 8, and 10, respectively. Lens 58 expands the diameter of entering light signal 22 into new light signal 66. Similarly, lens 60 expands the diameter of signal 24 into new signal 68. While the lenses of lens array 56 alter the size of the light signals, they do not alter the center spacing of the signals and thus conserve the spatial characteristics of the array emitted by VCSEL structure 2.

In FIG. 7(b) lens array 70 contains lenses 72, 74, 76, and 78 that correspond spatially to emission apertures 4, 6, 8, and 10, respectively. Lens 72 expands the diameter and changes the direction of entering light signal 22 into new light signal 80. Similarly, lens 74 expands the diameter and changes the direction of signal 24 into new signal 82. In this particular example, lens array 70 diverges entering light signals, though other configurations of divergence or convergence could be used as well.

In the second preferred embodiment, the timing of illuminating the individual elements is an integral part of the sensing process. The elements are serially illuminated in a sequence whose temporal characteristics are interpreted. In FIG. 8, VCSEL structure 2 is shown sequentially emitting light signals from

emission apertures 4, 6, 8, and 10 in the order 4, 6, 8, 10, 4, 6, 8, 10, etc. Corresponding light signals 22, 24, 26, and 28 are, therefore, emitted from the emission apertures. In this example, three light signals have already been emitted (26, 28, 22), illustrated by the dotted lines, and one is currently lit (24). Light signal 26 has been emitted and has reached detector 32 unobstructed by target 30. Signal 28 was then emitted and similarly reached detector 32 obstructed. Light signal 22 reached target 30 next, also unobstructed. Currently, signal 24 is lit and has been blocked by target 30 before reaching detector 32. If the output of a single detector 32 disposed to receive all of the light signals in the array is monitored over time, the angular (and to a partial extent, the spatial) location of target 30 can be determined by the absence of a signal at the time the particular signal(s) are blocked. The array need not be circular, as linear arrays or multiple concentric rings could be used to map the shape of target 30 by interpreting the time-sequence of the output of detector 32.

If optics are added, as depicted in FIG. 9, light signals can be steered into different angles. Light signals are shown passing through lens 30, positioned between VCSEL structure 2 and target 84. Lens 30 then redirects the light signals to different places in the environment, allowing a single detector 32 to sense targets 84 at widely separated locations. With only ten VCSEL elements, approximately, a full half-plane of 2π steradians could be monitored.

In this example, light signals 28, 22, and then 24 have already been sequentially emitted, as denoted by the dotted lines, and light signal 26 is currently lit. After being redirected by lens 30, light signal 26 travels until it intercepts target 84. Light signal 26 then reflects off of target 84 and reaches detector 32. It should be noted that target 84 happened to be positioned in the environment such that it lay in the path of light signal 26, rather than light signal 26 specifically seeking target 84. If target 84 were moved, it would lie in the path

of a different light signal.

With linear arrays, position of a target along an axis can be detected. One example of a "circular" array application could use a single lens above VCSEL structure 2. This lens could skew each signal into a different angle as the individual elements are sequentially illuminated. A light signal can, therefore, be directed to different areas in an environment at different times by simply illuminating different elements at different times. Measuring the temporal output of a detector disposed to collect reflected light signals can provide information on the presence of a target and of its location. Even if location information is not necessary, the effective scanning of a light signal without moving parts can provide for a purely electrical function rather than a mechanical function. This feature allows for operation at a much lower input power, which could be important in battery-powered applications where energy conservation is often critical.

A lens or array of lenses can be positioned near VCSEL structure 2 such that a lens collimates each light signal passing through. Whereas current optical systems are generally known to collimate a single light signal into one parallel group of signals, the present invention can collimate each of a plurality of signals into corresponding parallel groups. Since each light signal passes through a lens at a different angle, due to the different location of each emission aperture on VCSEL structure 2, each group of collimated signals exits a lens at a different angle.

An optical sensing system for detecting target motion within a known environment is now described. Referring to FIG. 10, a system capable of detecting target motion can include a vertical cavity surface emitting laser structure 105 with at least two emission apertures that could be defined by known processing methods

such as photolithography. A laser signal can be emitted into an environment 100 from each of the emission apertures. The system can also include at least one detector 103 that is operationally responsive to the vertical cavity surface emitting laser structure 105. The system can include a microprocessor 101 that is operationally coupled to the detector(s) 103, VCSEL 105 and a memory 102, such as a database, for storing target data and a training module for allowing the system to be trained to recognize targets 110. The trainable laser optical sensing system can make positive identification of object once trained where microprocessor 101 references a database 102 and/or using neural network capabilities to correlate the detected pattern of light signals from the target 110 with stored patterns of signals from known targets. A motion analysis module 107 enables the microprocessor 101 to determine target mobility characteristics (e.g., velocity, direction). The motion analysis module 107 determines motion characteristics of an object detected within said environment where the laser source 105 emits at least two laser signals into an environment occupied by a target 110, at least one detector 103 detects changes in said at least two laser signals after signals pass through environment 100 and interfere with a detected object 110, and microprocessor 101 determines target characteristics based on signals received by detector 103 and input from said motion analysis module 107. The laser optical sensing system can also include a training module 106. The training module would include software used by the microprocessor 101 during training and detection operations.

Referring to FIG. 11, during operation the vertical cavity surface emitting laser structure can emit at least two laser signals into the environment 111, which may be occupied by a target in motion. At least one detector detects the presence of (receives) the laser signals 112 once they have passed through the target-filled environment and are blocked by at least one target. The microprocessor processes 113 received signals associated with target motion using a motion analysis algorithm provided to the microprocessor by a motion analysis module. The microprocessor

then determines target motion 114 based on analysis of received target data. Optics can also be added to the system, such that laser signals pass through at least one lens or reflect off of a mirror or mirrors after exiting the emission apertures.

The system can be trained or calibrated by emitting at least one laser signal at a time into an environment containing a known target (known target in motion characteristics) using a vertical cavity surface emitting laser structure. Motion characteristics of the known target can be referred to as a test target. The test target interferes with laser signals. Signal reflected off of said test target are received by at least one detector. The laser signals, representing target characteristics, are processed by the microprocessor and used to calibrate the motion analysis module by storing results in memory.

Target motion and characteristic information can be determined by placing a single detector 103 in the room, positioned near to or far from VCSEL structure 105, though a plurality of detectors could be used as well. A lens or array of lenses (as shown in FIG. 9) could also be placed near detector 103 to effectively expand the area from which it can receive light signals. As detector(s) receives light signals reflected off of the target 110 and/or the walls or other objects in the room (environment 100), the microprocessor 101 processes the signals to provide the desired information.

It should be noted that nearly all of the aforementioned applications, as well as any others, could potentially be addressed using either transmissive or reflective systems. The embodiments and examples set forth herein are presented to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. Those skilled in the art, however, will recognize that the foregoing description and examples have been presented for the purpose of illustration and example only.

Other variations and modifications of the present invention will be apparent to those of skill in the art, and it is the intent of the appended claims that such variations and modifications be covered. The description as set forth is not intended to be exhaustive or to limit the scope of the invention. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims. It is contemplated that the use of the present invention can involve components having different characteristics. It is intended that the scope of the present invention be defined by the claims appended hereto, giving full cognizance to equivalents in all respects.

20